

## AMAXX® combination unit

Part no. 920024




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST

## Technical specifications

|                           |   |
|---------------------------|---|
| CEE 16 A, 5 p, 400 V      | 2   |
| SCHUKO® 16 A, 230 V       | 2   |
| Connection / feeder cable | • for 1 cable up to 5 x 10 mm <sup>2</sup> and 1 cable up to 3 x 10 mm <sup>2</sup> |
| Protection type           | IP 44   |
| Enclosure material        | Plastic   |
| Weight                    | 2680 g  |
| Height                    | 260 mm  |
| Width                     | 225 mm  |

## Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.