

AMAXX® combination unit
Part no. 920033




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

| | | |
|---------------------------|---------|--|
| SCHUKO® 16 A, 230 V | 4 | |
| Fusing | | • 1 RCD 25 A, 2 p, 0.03 A |
| Pre-fuse max. | 16 A | |
| InA | 16 A | |
| RDF | 1 | |
| Connection / feeder cable | | • 2 m H07RN-F3G1.5 with plug SCHUKO® 16 A, 230 V |
| Protection type | IP 44 | |
| Enclosure material | Plastic | |
| Weight | 2140 g | |
| Height | 260 mm | |
| Width | 225 mm | |

Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

| Receptacles | Degrees | Depth |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44 | 175 mm |
| | IP 67 | 194 mm |
| CEE 16A, 3p, 230V | IP 44 | 204 mm |
| | IP 67 | 205 mm |
| CEE 16A, 5p, 400V | IP 44 | 209 mm |
| | IP 67 | 213 mm |
| CEE 32A, 5p, 400V | IP 44 | 221 mm |
| | IP 67 | 227 mm |
| CEE 63A, 5p, 400V | IP 44 | 248 mm |
| | IP 67 | 248 mm |

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.