

**AMAXX® combination unit**  
Part no. 941265




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- MENNEKES AMAXX® combination unit for camp sites already comply to the standard and regulations which came into force 01.07.2007 according to DIN VDE 0100-708\_2006-02 and DIN VDE 0100-754:2006-02

**Technical specifications**

CEE 16 A, 3 p, 230 V	4
Fusing	<ul style="list-style-type: none"> <li>• 4 RCD's 25 A, 2 p, 0.03 A</li> <li>• 4 MCB's 16 A, 1 p, B</li> </ul>
Pre-fuse max.	63 A
InA	32 A
RDF	1
Connection / feeder cable	<ul style="list-style-type: none"> <li>• for 2 cables up to 5 x 25 mm<sup>2</sup></li> </ul>
Protection type	IP 44
Enclosure material	Plastic
Weight	5986 g
Height	520 mm
Width	225 mm

**Drawing**



**Drawing 1 MB 523**

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	186 mm
	IP 67	208 mm
CEE 16A, 3p, 230V	IP 44	216 mm
	IP 67	220 mm
CEE 16A, 5p, 400V	IP 44	222 mm
	IP 67	226 mm
CEE 32A, 5p, 400V	IP 44	231 mm
	IP 67	236 mm
CEE 63A, 5p, 400V	IP 44	260 mm
	IP 67	260 mm

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.