

## Industrial Network Distributor


Part no. 25405



### Technical specifications

SCHUKO® 16 A, 230 V	2
Data port sockets	1 Cepex data port receptacle (black RAL 9005) with 2 RJ45 right angle connector modules for direct connection of patch cables
Fitted with	<ul style="list-style-type: none"> <li>Patch and mounting panel with threaded ground bolt M6 for the optional connection of an external ground conductor</li> </ul>
Connection / feeder cable	<ul style="list-style-type: none"> <li>4 Velcro connectors for fastening installed components on the base plate</li> <li>2 screw fittings M 40 with multiple seal, 6 openings for a cable diameter of 6-9 mm including 5 each blanking plugs</li> <li>1 screw fitting M 20</li> <li>1 screw set</li> </ul>
Protection type	IP 44
Shutter	false
Enclosure material	Plastic
Weight	4350 g
Height	520 mm
Width	225 mm

### Drawing



Drawing 1 MB 523

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	186 mm
	IP 67	208 mm
CEE 16A, 3p, 230V	IP 44	216 mm
	IP 67	220 mm
CEE 16A, 5p, 400V	IP 44	222 mm
	IP 67	226 mm
CEE 32A, 5p, 400V	IP 44	231 mm
	IP 67	236 mm
CEE 63A, 5p, 400V	IP 44	260 mm
	IP 67	260 mm

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.