

Panel mounted inlet

Part no. 2692



- screw terminals
- high heat resistant contact carrier
- nickel plated contacts
- with hinged lid

Technical specifications

Ampere	32 A
Poles	4 p
Voltage	400-440 V
Clock position	3 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	nickel plated contacts, highly heat resistant contact carrier
Protection type	IP 67
Weight	354 g
Declaration of Conformity	VDE, EAC

Drawing



Drawing	Amp.	16				32		63	
		Z MB 40		Poles		3	4	5	4
Dim. in mm	a	85	85	85	85	114	114	114	114
	b	85	85	85	85	114	114	114	114
	c	141	141	141	144	180	180	180	180
	d	70	70	70	70	90	90	90	90
	e	70	70	70	70	90	90	90	90
	f	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	g	6	6	6	6	6	6	6	6
	g.1	2	2	2	2	2	2	2	2
	h	181	181	181	188	242	242	242	242
	s	86	93	93	100	113	113	113	113
	l	30	30	30	30	40	40	40	40
Terminal for cond. cross section (mm ²) min.-max.	1	2.5	2.5	2.5	2.5	4	4	4	4
		-2.5	-6	-6	-6	-16	-16	-16	-16