

Wall mounted socket

Part no. 128A



Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 63 A |
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | X-CONTACT® |
| Protection type | IP 67 |
| Weight | 909 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing

| Drawing 1 MB 112 | Amp. Poles | 63 | | |
|---------------------|--|----------------------------|-------|-------|
| | | 3 | 4 | 5 |
| Dim. in mm | a | 170 | 170 | 170 |
| | b | 118 | 118 | 118 |
| | c | 175 | 175 | 175 |
| | d | 134.5 | 134.5 | 134.5 |
| | e | 103 | 103 | 103 |
| | f | 6.1 | 6.1 | 6.1 |
| | g | 6 | 6 | 6 |
| | h | 219 | 219 | 219 |
| | M | 40 | 40 | 40 |
| | M* | 2x40 (blind) to be cut out | | |
| | Max. cable diam. (mm) | 27 | 27 | 27 |
| | Terminal for cond. cross section (mm²) min.-max. | 6 | 6 | 6 |
| | | -25 | -25 | -25 |