

Connector PowerTOP® Xtra

Part no. 14107



- screw terminals
- with rubberised grip area
- frame terminals
- **X-CONTACT**
- highly heat resistant contact carrier
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides
- products with pilot contact on request

Technical specifications

| | |
|---------------------------|---|
| Ampere | 63 A |
| Poles | 4 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, X-CONTACT® |
| Protection type | IP 44 |
| Weight | 800 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing 3 MB 69 | Amp. Poles | 63 | | |
|--------------------------------------|---------------|-----|-----|-----|
| | | 3 | 4 | 5 |
| Dim. in mm | a | 268 | 268 | 268 |
| | b | 95 | 95 | 95 |
| | h | 109 | 109 | 109 |
| | y | 36 | 36 | 36 |
| Terminal for cond. cross | | 6 | 6 | 6 |
| section (mm ²) min.-max. | | —16 | —16 | —16 |