

**Connector PowerTOP® Xtra**  
Part no. 14233




- screw terminals
- with rubberised grip area
- frame terminals
- **X-CONTACT**
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

|                           |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| Ampere                    | 125 A                                                                     |
| Poles                     | 4 p                                                                       |
| Voltage                   | 400 V                                                                     |
| Clock position            | 6 h                                                                       |
| Hertz                     | 50-60 Hz                                                                  |
| Connection technology     | Screw terminals                                                           |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts, X-CONTACT® |
| Protection type           | IP 67                                                                     |
| Weight                    | 1554 g                                                                    |
| Declaration of Conformity | VDE, EAC                                                                  |

Drawing



| Drawing<br>3 MB 68       | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                          |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm               | a             | 270 | 270 | 270 | 310 | 310 | 310 |
|                          | b             | 113 | 113 | 113 | 125 | 125 | 125 |
|                          | h             | 123 | 123 | 123 | 135 | 135 | 135 |
|                          | y             | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm²) min.-max.  |               | —16 | —16 | —16 | —50 | —50 | —50 |