

**Plug AM-TOP®**

Part no. 2114



- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 4 p             |
| Voltage                   | 600-690 V       |
| Clock position            | 5 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 274 g           |
| Declaration of Conformity | EAC, CQC        |

**Drawing**



| Drawing<br>2 MB 217 | Amp.<br>Poles                        | 16    |       |       | 32  |     |      |
|---------------------|--------------------------------------|-------|-------|-------|-----|-----|------|
|                     |                                      | 3     | 4     | 5     | 3   | 4   | 5    |
| Dim. in mm          | a                                    | 142   | 147   | 147   | 186 | 186 | 180  |
|                     | b                                    | 53    | 59    | 67    | 70  | 70  | 77   |
|                     | h                                    | 59    | 69.4  | 76    | 81  | 81  | 89.5 |
|                     | n                                    | 105.2 | 110.5 | 110.5 | 141 | 141 | 135  |
|                     | y                                    | 14.5  | 16    | 16    | 22  | 22  | 22   |
|                     | Terminal for cond. cross             | 1     | 1     | 1     | 2.5 | 2.5 | 2.5  |
|                     | section (mm <sup>2</sup> ) min.-max. | -2.5  | -2.5  | -2.5  | -6  | -6  | -6   |