

**Plug AM-TOP®**  
Part no. 2243




- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 50-500 V        |
| Clock position            | 2 h             |
| Hertz                     | 300-500 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 171 g           |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>2 MB 217      |   | 16    |       |       | 32    |     |      |
|--------------------------|---|-------|-------|-------|-------|-----|------|
|                          |   | Poles |       |       | Poles |     |      |
|                          |   | 3     | 4     | 5     | 3     | 4   | 5    |
| Dim. in mm               | a | 142   | 147   | 147   | 186   | 186 | 180  |
|                          | b | 53    | 59    | 67    | 70    | 70  | 77   |
|                          | h | 59    | 69.4  | 76    | 81    | 81  | 89.5 |
|                          | n | 105.2 | 110.5 | 110.5 | 141   | 141 | 135  |
|                          | y | 14.5  | 16    | 16    | 22    | 22  | 22   |
| Terminal for cond. cross |   | 1     | 1     | 1     | 2.5   | 2.5 | 2.5  |
| section (mm²) min.-max.  |   | —2.5  | —2.5  | —2.5  | —6    | —6  | —6   |