

**Connector TM**  
Part no. 24686




- screw terminals
- with highly heat resistant contact carrier
- nickel plated contacts
- with protective cap
- (form DS)

Technical specifications

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| Ampere                | 16 A                                                          |
| Poles                 | 5 p                                                           |
| Voltage               | 230 V                                                         |
| Clock position        | 9 h                                                           |
| Hertz                 | 50-60 Hz                                                      |
| Connection technology | Screw terminals                                               |
| Contact               | highly heat resistant contact carrier, nickel plated contacts |
| Protection type       | IP 67                                                         |
| Weight                | 284 g                                                         |

Drawing



| Drawing<br>3 MB 73       | Amp.<br>Poles | 16   |      | 32  |     |
|--------------------------|---------------|------|------|-----|-----|
|                          |               | 3    | 5    | 3   | 5   |
| Dim. in mm               | a             | 160  | 170  | 204 | 205 |
|                          | b             | 70   | 87   | 101 | 101 |
|                          | h             | 78   | 94   | 98  | 105 |
|                          | y             | 14.5 | 16   | 22  | 22  |
| Terminal for cond. cross |               | 1    | 1    | 2.5 | 2.5 |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —6  | —6  |