

## Panel mounted socket with TwinCONTACT

Part no. 3573



- screwless spring terminals
- standard flange dimensions
- suitable for through wiring
- 20° inclination
- sockets optional fitted with auxiliary contact

### Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 32 A                    |
| Poles                     | 3 p                     |
| Voltage                   | 230 V                   |
| Clock position            | 6 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 67                   |
| Flange                    | 85x85 mm                |
| Fixing hole               | 70x70 mm                |
| Inclination               | 20 °                    |
| Weight                    | 246 g                   |
| Declaration of Conformity | EAC, CQC                |

### Drawing



| Drawing<br>1 MB 520  | Amp.<br>Poles | 16  |     |     | 32  |     |     |
|--|---------------|-----|-----|-----|-----|-----|-----|
|  |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm   | a             | 85  | 85  | 85  | 85  | 85  | 85  |
|  | b             | 85  | 85  | 85  | 85  | 85  | 85  |
|  | c             | 56  | 59  | 59  | 64  | 64  | 71  |
|  | d             | 70  | 70  | 70  | 70  | 70  | 70  |
|  | e             | 70  | 70  | 70  | 70  | 70  | 70  |
|  | f             | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|  | g             | 8   | 8   | 8   | 8   | 8   | 8   |
|  | g.1           | 2   | 2   | 2   | 2   | 2   | 2   |
|  | h             | 87  | 91  | 99  | 103 | 103 | 110 |
|  | i             | 78  | 85  | 89  | 103 | 103 | 106 |
|  | k             | 32  | 32  | 33  | 44  | 44  | 49  |
|  | l min.        | 57  | 64  | 70  | 78  | 78  | 78  |
|  | l max.        | 76  | 76  | 76  | 78  | 78  | 78  |
| Terminal for cond. cross<br>section (mm <sup>2</sup> ) min.-max. |               | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|  |               | -4  | -4  | -4  | -6  | -6  | -6  |