

Connector PowerTOP®

Part no. 3881




- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

Technical specifications

| | |
|---------------------------|---------------------------------------|
| Ampere | 16 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier |
| Protection type | IP 67 |
| Weight | 310 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing 3 MB 48/3 | Amp. Poles | 16 | | | 32 | | |
|--------------------------------------|---------------|------|------|------|------|------|------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 171 | 182 | 194 | 217 | 217 | 229 |
| | b | 78 | 85 | 96 | 103 | 103 | 110 |
| | h | 79 | 88 | 95 | 99 | 99 | 105 |
| | y | 19 | 19 | 22 | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm ²) min.-max. | | -2.5 | -2.5 | -2.5 | -6 | -6 | -6 |