

Plug PowerTOP®

Part no. 3936



screw terminals


•

- highly heat resistant contact carrier
 - nickel plated contacts
- cable gland and external cable grip

Technical specifications

| Ampere | 16 A |
|---------------------------|---|
| Poles | 5 p |
| Voltage | 230 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 44 |
| Weight | 241 g |
| Declaration of Conformity | EAC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | |
|------------------------------------|-------|------|------|------|------|------|------|
| 2 MB 174 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 162 | 172 | 186 | 199 | 199 | 213 |
| | b | 54 | 60 | 69 | 72 | 72 | 79 |
| | h | 60 | 67 | 77 | 83 | 83 | 91 |
| | n | 126 | 136 | 149 | 154 | 154 | 169 |
| | у | 19 | 19 | 22 | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm ²) minmax. | | -2.5 | -2.5 | -2.5 | 6 | —6 | —6 |