

**Hanging connector PowerTOP®**  
Part no. 3999




- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip
- hanging clip

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 5 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 450 g           |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>3 MB 51/3     | Amp.<br>Poles | 16   |      |      | 32   |      |      |
|--------------------------|---------------|------|------|------|------|------|------|
|                          |               | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm               | a             | 165  | 180  | 190  | 214  | 214  | 223  |
|                          | b             | 60   | 68   | 76   | 82   | 82   | 89   |
|                          | h             | 76   | 84   | 90   | 92   | 92   | 99   |
|                          | y             | 19   | 19   | 22   | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross |               | 1    | 1    | 1    | 2.5  | 2.5  | 2.5  |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —2.5 | —6   | —6   | —6   |