

Cepex wall mounted socket
Part no. 4167




- screw terminals
- with labelling field
- with safety lock, two keys
- cannot be dismantled when locked
- on request with identical locks
- with identical lock: part no. + index G

Technical specifications

| | |
|---------------------------|----------|
| Ampere | 32 A |
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Protection type | IP 44 |
| Shutter | false |
| Weight | 402 g |
| Declaration of Conformity | EAC |

Drawing



| | | | | | | | |
|--------------------------|-------|--------|--------|--------|--------|--------|--------|
| Drawing | Amp. | 16 | | | 32 | | |
| 1 MB 313 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 93 | 93 | 93 | 93 | 93 | 93 |
| | b | 90 | 90 | 90 | 90 | 90 | 90 |
| | c | 90 | 90 | 90 | 102 | 102 | 102 |
| | d | 75 | 75 | 75 | 75 | 75 | 75 |
| | e | 73 | 73 | 73 | 73 | 73 | 73 |
| | f | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| | g | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 |
| | k | 36 | 36 | 36 | 36 | 36 | 36 |
| | y | 25.5 | 25.5 | 25.5 | 25.5 | 25.5 | 25.5 |
| | M | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 |
| Terminal for cond. cross | | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max. | | —4 | —4 | —4 | —6 | —6 | —6 |