

Wall mounted socket  
Part no. 5695A




- screw terminals
- **X-CONTACT**
- switched
- mechanical DUO-interlock
- 3 pole fuse socket NH 00
- upon request with provision for an additional padlock

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 125 A           |
| Poles                     | 5 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | X-CONTACT®      |
| Protection type           | IP 67           |
| Enclosure material        | Plastic         |
| Weight                    | 8840 g          |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>1 MB 177                              | Amp.<br>Poles | 125    |        |        |
|--|---------------|--------|--------|--------|
|  |               | 3      | 4      | 5      |
| Dim. in mm                                       | a             | 460    | 460    | 460    |
|  | b             | 260    | 260    | 260    |
|  | c             | 270    | 270    | 270    |
|  | d             | 434    | 434    | 434    |
|  | e             | 234    | 234    | 234    |
|  | f             | 11     | 11     | 11     |
|  | g             | 9      | 9      | 9      |
|  | h             | 519    | 519    | 519    |
|  | M             | 63     | 63     | 63     |
|  | M*            | 2x63   | 2x63   | 2x63   |
| Max. cable diam. (mm)                            |               | 44     | 44     | 44     |
| Terminal for cond. cross section (mm²) min.-max. |               | 25 —70 | 25 —70 | 25 —70 |