

Part no. 5743A



- screw terminals
- switched
- mechanical DUO-interlock
- sockets can be padlocked

Technical specifications

Amperere	32 A
Poles	3 p
Voltage	110 V
Clock position	4 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Enclosure material	Plastic
Weight	1134 g
Declaration of Conformity	EAC, CQC

The technical drawing shows two views of the M6000 series pressure washer. The left view is a top-down perspective showing the rectangular body with dimensions: width b , height d , and distance from the top edge to the trigger gun attachment point e . The right view is a side profile showing the motor housing with dimensions: total length c , mounting bracket height g , motor diameter ϕd , and a 25° angle on the lower section. A dimension M^* indicates the distance from the bottom edge to the base of the motor housing.

Drawing 1 MB 174 Dim. in mm	Amp. Poles	16			32		
		3	4	5	3	4	5
a		225	225	225	225	225	225
b		118	118	118	118	118	118
c		141	141	141	146	146	146
d		208	208	208	208	208	208
e		101	101	101	101	101	101
f		6.3	6.3	6.3	6.3	6.3	6.3
g		8	8	8	8	8	8
h		250	252	254	264	264	264
M		1x25 and 1x32			1x25 and 1x32		
Mx2		2x25	2x25	2x25	2x25	2x25	2x25
Max. cable diam. (mm)		25	25	25	25	25	25
Terminal for cond. cross section (mm ²) min.-max.		1.5 — 1.5	1.5 — 2.5	1.5 — 2.5	2.5 — 2.5	2.5 — 2.5	2.5 — 2.5
		—4 — 4	—4 — 4	—4 — 4	—10 — 10	—10 — 10	—10 — 10