

## Wall mounted socket

Part no. 597




- screw terminals
- internal fixing
- one cable entry at top and two blind entries (can be cut out) at bottom lower part of enclosure base can be turned 180°

## **Technical specifications**

| Ampere                    | 32 A            |
|---------------------------|-----------------|
| Poles                     | 3 p             |
| Voltage                   | 20-25 V         |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 278 g           |
| Declaration of Conformity | EAC             |

## Drawing



| Drawing         | Amp.      | 1                          | 16  |                            |      | 32      |  |
|-----------------|-----------|----------------------------|-----|----------------------------|------|---------|--|
| 1 MB 137        | Poles     | 2                          | 3   |                            | 2    | 3       |  |
| Dim. in mm      | а         | 128                        | 128 |                            | 128  | 128     |  |
|                 | b         | 84                         | 84  |                            | 84   | 84      |  |
|                 | c         | 120                        | 120 |                            | 120  | 120     |  |
|                 | d         | 11                         | 11  |                            | 11   | 11      |  |
|                 | е         | 68                         | 68  |                            | 68   | 68      |  |
|                 | f         | 5.3                        | 5.3 |                            | 5.3  | 5.3     |  |
|                 | g.        | 4                          | 4   |                            | 4    | 4       |  |
|                 | ĥ         | 146                        | 146 |                            | 146  | 146     |  |
|                 | M         | 25                         | 25  |                            | 32   | 32      |  |
|                 | M*        | 2x25 (blind) to be cut out |     | 2x25 (blind) to be cut out |      | cut out |  |
| Max. cable dian | n. (mm)   | 18                         | 18  |                            | 25   | 25      |  |
| Terminal for co | nd. cross | 4                          | 4   |                            | 4    | 4       |  |
| section (mm2) n | ninmax.   | —2x6                       | 10  |                            | —2x6 | -10     |  |