

## Wall mounted inlet

Part no. 921



- screw terminals
- enclosure base with stamped recess for quick cutting out

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 4 p             |
| Voltage                   | 50-500 V        |
| Clock position            | 10 h            |
| Hertz                     | 100-300 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 237 g           |
| Declaration of Conformity | EAC, CQC        |

## Drawing



| Drawing   | Amp. | 16                         |      |      | 32                         |       |       |
|---|------|----------------------------|------|------|----------------------------|-------|-------|
|   |      | Poles                      |      |      | Poles                      |       |       |
| 2 MB 32   |      | 3                          | 4    | 5    | 3                          | 4     | 5     |
| Dim. in mm  | a    | 87                         | 100  | 100  | 128                        | 128   | 128   |
|   | b    | 64                         | 75   | 75   | 84                         | 84    | 84    |
|   | c    | 93                         | 106  | 110  | 133                        | 133   | 135   |
|   | d    | 40                         | —    | —    | —                          | —     | —     |
|   | d1   | —                          | 10.5 | 10.5 | 11                         | 11    | 11    |
|   | e    | 50.5                       | 59   | 59   | 68                         | 68    | 68    |
|   | f    | 4.5                        | 5    | 5    | 5.3                        | 5.3   | 5.3   |
|   | g    | 4                          | 4    | 4    | 4                          | 4     | 4     |
|   | h    | 122                        | 133  | 135  | 169                        | 169   | 170   |
|   | M    | 20                         | 20   | 20   | 32                         | 32    | 32    |
|   | M*   | 1x20 (blind) to be cut out |      |      | 2x25 (blind) to be cut out |       |       |
| Max. cable diam. (mm)   |      | 15                         | 15   | 15   | 18/25                      | 18/25 | 18/25 |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |      | 1                          | 1    | 1    | 2.5                        | 2.5   | 2.5   |
|   |      | -2.5                       | -2.5 | -2.5 | -6                         | -6    | -6    |