

Connector CEEplus®

Part no. 928




- screw terminals
- with 4 additional contacts
- cable gland and sealing
- strain relief and protection against kinking enclosure with thread lock and safety slide •

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------|
| Poles | 3 p+a |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 212 g |
| Declaration of Conformity | EAC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | |
|------------------------------------|-------|------|------|------|-----|-----|-----|
| 3 MB 60 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 160 | 174 | 172 | 214 | 214 | 210 |
| | b | 57 | 61 | 69 | 75 | 75 | 80 |
| | h | 83 | 92 | 98 | 100 | 100 | 108 |
| | У | 16 | 16 | 16 | 22 | 22 | 22 |
| | | | | | | | |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm ²) minmax. | | -2.5 | -2.5 | -2.5 | —6 | —6 | —6 |