

DELTA-BOX combination unit

Part no. 92908





- pre-wired for installation
- with cable grip and installed hanging hook enclosure and insert made of AMAPLAST

Technical specifications

| CEE 16 A, 5 p, 400 V | 1 |
|---------------------------|---|
| SCHUKO® 16 A, 230 V | 2 |
| Connection / feeder cable | 2 m H07RN-F5G2.5 with CEE-plug 16 A, 5 p, 400 V |
| Protection type | IP67 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 1745 g |
| Declaration of Conformity | EAC |

Drawing





| 3 MB 45 | | | |
|---------|----------------------|------------|----------|
| Pos. | Receptacles | IP-degrees | Dim. |
| a | | | 114.0 mm |
| a1 | SCHUKO®, 16 A, 230 V | IP 68 | 35.0 mm |
| a1 | CEE 16 A, 3 p, 230 V | IP 67 | 56.3 mm |
| a1 | CEE 16 A, 5 p, 400 V | IP 67 | 59.0 mm |
| a2 | | | 30.0 mm |
| b | | | 160.0 mm |
| b1 | SCHUKO®, 16 A, 230 V | IP 44 | 24.0 mm |
| b1 | CEE 16 A, 3 p, 230 V | IP 44 | 44.3 mm |
| b1 | CEE 16 A, 5 p, 400 V | IP 44 | 47.0 mm |
| С | | | 133.0 mm |
| d | | | 97.0 mm |
| V | | | 17.0 mm |