

Plug PowerTOP Xtra

Part no. 13248




- screw terminals
- rubberized grip area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

| | |
|-----------------------|---|
| Ampere | 63 A |
| Poles | 5 p |
| Voltage | 50-500 V |
| Clock position | 1 h |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP67 |
| Weight | 882 g |
| Certifications | VDE, EAC, CQC |

Drawing



| Drawing 2 MB 225 | Amp. Poles | 63 | | | 125 | | |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 250 | 250 | 250 | 290 | 290 | 290 |
| | b | 114 | 114 | 114 | 130 | 130 | 130 |
| | y | 36 | 36 | 36 | 49 | 49 | 49 |
| Terminal for cond. cross | | 6 | 6 | 6 | 25 | 25 | 25 |
| section (mm ²) min.-max. | | -16 | -16 | -16 | -50 | -50 | -50 |