

## Connector PowerTOP Xtra S with SafeCONTACT

Part no. 14521




- screwless, with insulation displacement technology SafeCONTACT
- **X-CONTACT®**
- ergonomic enclosure design with nubbed grip zones
- rubberised cable gland with sealing
- strain relief and protection against kinking
- thread lock and safety slide
- area for self-adhesive labels
- the PowerTOP® Xtra S connector replaces the StarTOP connector 980

### Technical specifications

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screwless - SafeCONTACT
Contact	X-CONTACT
Protection type	IP54
Weight	188 g
Certifications	VDE, EAC, CQC

### Drawing



Drawing	Amp.	16			32		
		3	4	5	3	4	5
<b>3 MB 79</b>	<b>Poles</b>						
Dim. in mm	a	165	177	174	211	211	209
	b	55	68	69	78	78	80
	h	72	93	98	100	100	108
y min. from		7	8	8	10.5	10.5	13.5
	to max. mm	-13	-15.5	-15.5	-18	-18	-20
Terminal for cond. cross		1	1	1	2.5	2.5	2.5
section (mm <sup>2</sup> ) min.-max.		-2.5	-2.5	-2.5	-6	-6	-6