

Panel mounted socket TM

Part no. 24630




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- 20° inclination
- (form BS)

Technical specifications

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP67
Flange	85x85 mm
Fixing hole	70x70 mm
Inclination	20 °
Weight	176 g
Certifications	VDE

Drawing



Drawing 1MB474	Amp. Pole	16		32		63
		3	5	3	5	3/4/5
Dim. in mm	a	85	85	85	85	114
	b	85	85	85	85	114
	c	66	65	67	78	98
	d	70	70	70	70	90
	e	70	70	70	70	90
	f	5.5	5.5	5.5	5.5	6.5
	g	8	8	8	8	12
	g.1	2	2	2	2	2
	h	89	97	101	108	135
	i	70	87	94	101	113
	k	40	35	54	43	62
	l min.	57	70	78	78	92
	l max.	78	78	78	78	105
	o	20	20	20	20	15
Terminal for cond. cross section (mm²) min.-max.		1.5 1.5	1.5 2.5	2.5 2.5	2.5 2.5	6 6
		-4 -4	-10 -10	-10 -10	-10 -10	-25 -25